Application No.: 10/635,864 Response dated June 21, 2006 Reply to Office Action of: April 25, 2006

4097634201

-2-of7

## AMENDMENTS TO THE CLAIMS

A list of claims follows, including those to be amended:

- 1. (Currently Amended) A bimodal polyethylene comprising ethylene derived units and units derived from at least one of a C4 to C12 olefin; wherein the polyethylene has a density of from 0.940 to 0.970 g/cm<sup>3</sup>; an I<sub>21</sub>/I<sub>2</sub> of 80 or more; a residual zirconium or hafnium metal content of 2.0 ppm or less; a Mw/Mn of from 20 to 60; and wherein the polyethylene comprises a high molecular weight component and a low molecular weight component, the high molecular weight component present from 40 to 60 weight percent based on the total polyethylene, and wherein the high molecular weight component has a weight average molecular weight Mw of greater than 100,000 a.m.u.
- 2. (Original) The bimodal polyethylene of Claim 1, possessing an I<sub>2</sub> of 0.5 g/ 10 min or less.
- 3. (Original) The bimodal polyethylene of Claim 1, wherein the weight average molecular weight Mw of the high molecular weight component is greater than 150,000 a.m.u.
- 4. (Original) The bimodal polyethylene of Claim 1, wherein the weight average molecular weight Mw of the high molecular weight component is greater than 200,000 a.m.u.
- 5. (Currently Amended) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.8 1.5 ppm to 5.0 ppm or less.
- 6. (Original) The bimodal polyethylene of Claim 1, wherein the value of I21/I2 is greater than 90.

Application No.: 10/635,864 Response dated June 21, 2006

Reply to Office Action of: April 25, 2006

-3 - of 7

- 7. (Original) The bimodal polyethylene of Claim 1, possessing a notch tensile test result of greater than 150 hours at 3.0MPa.
- 8. (Original) The bimodal polyethylene of Claim 1, wherein a pipe with carbon black formed from the polyethylene is able to withstand at least 50 years at an ambient temperature of 20°C, using water as the internal test medium and either water or air as the outside environment (Hydrostatic (hoop) stress as measured by ISO TR 9080).
- Original) The bimodal polyethylene of Claim 1, wherein a pipe with carbon black formed from the polyethylene possesses a predicted S-4 T<sub>c</sub> for 110mm pipe of less than -5°C (ISO DIS 13477/ASTM F1589).
- (Original) The bimodal polyethylene of Claim 1, wherein a pipe with carbon black formed from the polyethylene possesses a predicted S-4 T<sub>c</sub> for 110mm pipe of less than -15°C (ISO DIS 13477/ASTM F1589).
- (Original) The bimodal polyethylene of Claim 1, wherein when formed into a
  0.5mil (13μ) film possesses an MD Tear of between about 5 g/mil and 25 g/mil.
- (Original) The bimodal polyethylene of Claim 1, wherein when formed into a
  0.5mil (13μ) film possesses an MD Tear of between about 15 g/mil and 25 g/mil.
- 13. (Original) The bimodal polyethylene of Claim 1 formed in a single reactor by contacting olefins and a catalyst composition comprising a Group 15 containing compound and a bulky ligand metallocene catalyst compound; wherein the Group 15 containing metal compound is represented by the formulae:

Application No.: 10/635,864 Response dated June 21, 2006

Reply to Office Action of: April 25, 2006

-4-of7

$$R^{3}$$
  $L$   $R^{1}$   $R^{6}$   $R^{2}$   $R^{2}$   $R^{7}$   $R^{5}$ 

or

wherein M is a Group 4, 5 or 6 metal; each X is independently a leaving group;

y is 0 or 1;

n is the oxidation state of M;

m is the formal charge of the ligand comprising the YZL or YZL' groups;

L is a Group 15 or 16 element;

L' is a Group 15 or 16 element or Group 14 containing group;

Y is a Group 15 element;

Z is a Group 15 element,

R<sup>1</sup> and R<sup>2</sup> are independently a C<sub>1</sub> to C<sub>20</sub> hydrocarbon group, a heteroatom containing group having up to twenty carbon atoms, silicon, germanium, tin, lead, or phosphorus; wherein R<sup>1</sup> and R<sup>2</sup> may be interconnected to each other;

1999U026.US-CON3.RCE.amendment.6.21.06.doc

Application No.: 10/635,864 Response dated June 21, 2006

Reply to Office Action of: April 25, 2006

-5-of7

- R<sup>3</sup> is absent or a hydrocarbon group, hydrogen, a halogen, a heteroatom containing group;
- R<sup>4</sup> and R<sup>5</sup> are independently an alkyl group, an aryl group, substituted aryl group, a cyclic alkyl group, a substituted cyclic alkyl group, a cyclic arylalkyl group, a substituted cyclic arylalkyl group or multiple ring system; wherein R<sup>4</sup> and R<sup>5</sup> may be interconnected to each other;
- R<sup>6</sup> and R<sup>7</sup> are independently absent, or hydrogen, an alkyl group, halogen, heteroatom or a hydrocarbyl group; and
- R is absent, or is hydrogen, a Group 14 atom containing group, a halogen, a heteroatom containing group.
- 14. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.6 ppm to 5.0 ppm.
- 15. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.8 ppm to 5.0 ppm.
- 16. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 2.0 ppm to 5.0 ppm.
- 17. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.5 ppm to 2.0 ppm.
- 18. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.6 ppm to 2.0 ppm.
- 19. (New) The bimodal polyethylene of Claim 1, wherein the zirconium or hafnium metal residuals content is 1.8 ppm to 2.0 ppm.